



GENERAL DATA	
SWL	: 10 t
<u>Load to arms</u>	
- Front	: 6,8 t
- Aft	: 3,2 t
<u>Speeds:</u>	
- Recovery	: 20 m/min
- CT	: 120 m/min
List/ Trim	: 5° / 2°
Seastate	: Hsign = 3,1 m
Windspeed	: Vwind = 19 m/sec (Bft 5)
Applicable rule	: ABS / API

FOUNDATION LOADS	
CASE 1	: OFFLEAD
CASE 2	: SIDELEAD
- Loads for case 2 are with sidelead in +Y direction If sidelead is in -Y direction, the loadsituation is in mirror	

For Solas conditions the supportloads are with impactfactor 1 to the load.
For ABS/API the impact to the load is 2,15.

DO NOT SCALE

TOTAL MASS: app. 11260 kG

This drawing is for information only and must not be used for construction or fabrication, prior to final design.

F 201007 Update sup loads		REV		TITLE: ARR. & DECKFOUNDATIONS "PFH 100-CT"	
E 222007 UPDATE	AT	RV	AV	DATE: 12-07-'06	TOLERANCES NEN-ISO 2768-1
D 110107 BORDERS	RV	AV	AV	APPROVED: -	PROJECTION
C 210206 UPDATE	AT	AT	AT	SCALE: 1:30	DRAWING NUMBER
B 131106 UPDATE	AT	AT	AT	A-101804	SIZE A1
A 120106 UPDATE	AT	AT	AT	REVISION F	

NDM
NED-DECK MARINE
Survival Systems & Deck Equipment

Vollstraat 22
3711 RZ Barneveld
Tel: (+31) 362-42295
Fax: (+31) 362-49217

This drawing is the property of NED-DECK MARINE B.V. and may not be reproduced or distributed to third parties without their specific written consent.